

## LIQUIDTIGHT FLEXIBLE METAL CONDUIT (LFMC)

### HALOGEN FREE LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT EFF – LSZH (LOW SMOKE ZERO HALOGEN)

- Interlocked steel construction
- Hot dip galvanized steel core
- Low smoke, Non- toxic, None-halogen
- Coated with white PE
- Flame retardant
- UV resistant
- Accepts standard UL Listed liquid-tight connectors
- Suitable for schools, hospitals, airports, high rise buildings or underground tunnels
- Suitable for concrete embedment and direct burial



Catalog Number	Trade Size (Inch)	Inside Diameter (mm)		Outside Diameter (mm)		Bending Radius (mm)	Roll Length (mt)
		Min.	Max.	Min.	Max.		
E-EFF-050	½	15.70	16.3000	20.2000	20.7000	65	30
E-EFF-075	¾	20.70	21.2000	25.5000	26.1000	75	30
E-EFF-100	1	26.00	26.6000	31.6000	32.2000	100	30
E-EFF-125	1-¼	34.70	35.4000	40.8000	41.5000	125	15
E-EFF-150	1-½	40.00	40.6000	46.6000	47.2000	150	15
E-EFF-200	2	51.30	51.9000	58.1000	58.7000	175	15
E-EFF-250	2-½	62.90	63.3000	72.1000	73.0000	200	10
E-EFF-300	3	77.90	78.7000	87.9000	88.9000	225	10