

## ELECTROFLEX® FLEXIBLE STEEL CONDUIT – UL LISTED HEAVY DUTY

- Interlocked Steel construction
- Premium hot dip galvanized zinc coating for superior corrosion resistance
- Smooth interior for easy wire pull-through
- Extra flexibility for simplified positioning
- Listed connectors available from leading manufacturers
- RoHS WEEE compliant
- Complies with UL-1 File number E485125
- 5/16" and 3/8" RWS are also available upon request
- Suitable for heavy industrial applications such as; stadiums, airports, factories, public buildings, etc.



Catalog Number	Trade Size (inch)	Inside Diameter				Outside Diameter				Bending Radius		Roll Length (ft)
		Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)			
E-STL-050	½	0.625	15.88	0.645	16.38	0.860	21.84	0.920	23.37	3	75	100
E-STL-075	¾	0.812	20.62	0.835	21.21	1.045	26.54	1.105	28.07	4	100	100
E-STL-100	1	1.000	25.40	1.040	26.42	1.300	33.02	1.380	35.05	5	125	50
E-STL-125	1-¼	1.250	31.75	1.300	33.02	1.550	39.37	1.630	41.40	6-¼	155	50
E-STL-150	1-½	1.500	38.10	1.575	40.01	1.850	46.99	1.950	49.53	7-½	190	25
E-STL-200	2	2.000	50.80	2.080	52.83	2.350	59.69	2.450	62.23	10	250	25
E-STL-250	2-½	2.500	63.50	---	---	2.860	72.64	3.060	77.72	12-½	310	25
E-STL-300	3	3.000	76.20	---	---	3.360	85.34	3.560	90.42	15	175	25
E-STL-350	3-½	3.500	88.90	---	---	3.860	98.04	4.060	103.12	17-½	440	25
E-STL-400	4	4.000	101.60	---	---	4.360	110.74	4.560	115.82	20	500	25